



## ECHO S 125 WHITE

Instead of replacing with cover rings, choose a complete luminaire in the size you need. Echo is a large product family for holes from 103-300mm. Dimmable all-round luminaire for public environments that need a lot of light, such as in rooms with high ceilings, corridors or shops. Perfect for new installations and to replace compact fluorescent tube luminaires. Selectable colour temperature via DIP switch. Echo M and Echo L have adjustable lumen output via DIP-switch. Comes complete with driver for phase dimming or DALI-2. DALI-2 comes with Q-box Micro, push-in terminals and screwless strain relief. Dimmable with most common dimmers on the market.

### DESCRIPTION

<b>GTIN:</b>	7392971141282
<b>Item Name:</b>	Echo S 125 White
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	1150
<b>Light Source:</b>	LED
<b>Light Source Included:</b>	Yes
<b>Replaceability:</b>	Replaceable LED by professional, Replaceable Control gear by professional
<b>LED Colour:</b>	White
<b>Colour Temperature (K):</b>	3000, 4000, 5700
<b>Colour Rendering Index (Ra):</b>	>80
<b>Colour Consistency (SDCM):</b>	3
<b>Luminous Intensity (cd):</b>	720
<b>Beam Angle (°):</b>	80
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	1
<b>Number of LED (pcs):</b>	96
<b>Life Time:</b>	h Ta °C
<b>Nominal Life Time (h):</b>	50000
<b>Lumen maintenance 50 000h:</b>	L81
<b>Lumen maintenance 75 000h:</b>	L73
<b>LLMF @ 50 000h:</b>	0.81
<b>Life Time Driver:</b>	50 000h/10%
<b>Flicker (PstLM):</b>	0,003
<b>Stroboscopic effect (SVM):</b>	0,004

## TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Power LED (W):	12
Max. Power Luminaire (W):	14
Max. System Power (W):	14
Max. Efficiency Luminaire (lm/W):	82
Max. Efficiency System (lm/W):	82

Containing light source energy efficiency class (EU) 2019/2015: E

## OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Trailing Edge, Leading Edge
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Stand Alone
Driver Manufacturer:	Hide-a-lite
Connection (type):	Quick Terminal
Connection (mm <sup>2</sup> ):	3x0,5-2,5
Through Wiring:	Yes
Strain Relief:	Yes
Power Factor $\lambda$ :	0,9
Efficiency (%):	82
Power loss (W):	2,5
Leakage current (mA) (at 230 V, 50 Hz, full load):	0,5
Constant Current (mA):	350
Min. Ta (°C):	-20
Max. Ta (°C):	40
Max. Tc (°C):	85
Dimming secondary side:	AM
Suitable for random switching:	Yes
Inrush current (max/time):	2,88A 102 $\mu$ s
Mains surge protection DM (kV):	0,5
Mains surge protection CM (kV):	1
Fuse B10 (pcs):	40
Fuse B16 (pcs):	64
Fuse C10 (pcs):	68
Fuse C16 (pcs):	108

## COLOR AND MATERIAL

Material:	Aluminium
Color:	White
Environmental Assessment:	Byggvarubedömningen
Available in special color:	Yes

## MEASUREMENT AND INSTALLATION

<b>Operating Environment:</b>	Indoor / wet locations, Outdoor
<b>IP Degree of Protection:</b>	44
<b>Protection Class:</b>	II
<b>Installation:</b>	Built-in
<b>Mounting Installation:</b>	Mounting Spring
<b>Ceiling Thickness Interval (mm):</b>	5-40mm
<b>Fire Safety Marks:</b>	Not in insulation without protection cover
<b>Approval Marks:</b>	CE, a Hide-a-lite Choice
<b>Filament Test IEC 695-2-1(°C):</b>	650
<b>Height (mm):</b>	84
<b>Diameter (mm):</b>	124
<b>Weight (kg):</b>	0,53
<b>Min. Built-in (mm):</b>	300x200x95
<b>Height Recessed Part (mm):</b>	82
<b>Height Exterior Part (mm):</b>	2
<b>Built-in Ø (mm):</b>	102-113mm

