



WALLY G2 WHITE 2700K

Discrete, recessed and phase dimming 230V luminaire. Wall luminaire adapted for appliance box that creates distinct light distribution on the floor. For example, you can illuminate an indoor pathway or a staircase along a wall. Easily change the appearance of a luminaire with black front lid (sold separately). Integrated push-in terminal on the back for through wiring gives simple installation. Complete with integrated phase dimmable driver.

DESCRIPTION

GTIN:	7392971138978
Item Name:	Wally G2 White 2700K
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	195
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Non-replaceable LED, Non-replaceable Control gear
LED Colour:	Warm White
Colour Temperature (K):	2700
Colour Rendering Index (Ra):	>90
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	120
Beam Angle (°):	60
Light sharing:	Asymmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	L90 50000h Ta 25°C
Nominal Life Time (h):	50000
Lumen maintenance 50 000h:	L90
LLMF @ 50 000h:	0.9
Life Time Driver:	50 000h/5%

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50
Power LED (W):	2,9
Max. Power Luminaire (W):	3,6
Max. System Power (W):	3,6
Max. Efficiency Luminaire (lm/W):	54,2
Max. Efficiency System (lm/W):	54,2

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Trailing Edge
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm2):	3x0,5-1,5
Through Wiring:	Yes
Power Factor λ :	0,92
Efficiency (%):	79
Constant Current (mA):	200
Min. Ta (°C):	-20
Max. Ta (°C):	50
Max. Tc (°C):	80
Dimming secondary side:	AM
Protection Against:	Short Circuit, Overheating 100°C, Overload
Fuse B10 (pcs):	100
Fuse B16 (pcs):	160
Fuse C10 (pcs):	120
Fuse C16 (pcs):	180

COLOR AND MATERIAL

Material:	Aluminium
Color:	White
Environmental Assessment:	Byggvarubedömningen

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / damp locations
IP Degree of Protection:	21
Protection Class:	I
Installation:	Built-in
Mounting Installation:	Screw Mounting
Fire Safety Marks:	Not in insulation without protection cover
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Width (mm):	85
Height (mm):	85
Depth (mm):	41
Weight (kg):	0,155
Min. Built-in (mm):	Ø60x43
Height Recessed Part (mm):	38
Height Exterior Part (mm):	4
Built-in Ø (mm):	60mm

