





HEATSTRIP 24V IP67 2700K 2X2.5M

Heat-resistant LED strip for saunas that withstands up to 125°C and is intended for installation in zone 2 (0–1 m from floor) and zone 3 (up towards ceiling). Provides a pleasant light and can be customized in length. Available in ready-made lengths or by the meter.

Light Technical Data

Even light line creating an atmospheric illumination. Suitable for both functional and decorative lighting. Available in 2700K.

Technical data

LED strip 24V 8.4W/m. Lifetime: 35 000h Ta125°C.

Operation and Connection

Color and material

Measurement and installation

Quick and easy installation with press-fitting into plastic profile or clips. The close cutting interval of 50mm makes it easy to adjust length to sauna layout. Kits delivered in lengths of 2 x 2.5 m with 5 m connection cable and accessories for connection and mounting. For projects with specific requirements, custom lengths by the meter are available.

Controls

DESCRIPTION

GTIN:

7392971156637

Item Name:

Heatstrip 24V IP67 2700K 2x2.5m

Warranty:

5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	3900
Light Source:	LED
Replaceability:	Non-replaceable LED
LED Colour:	Warm White
Colour Temperature (K):	2700
Colour Rendering Index (Ra):	>90
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	1400
Beam Angle (°):	120
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	2400
Life Time:	h Ta °C
Nominal Life Time (h):	35000
Lumen maintenance 35 000h:	L70

TECHNICAL DATA

Voltage (type):	DC
Voltage Interval (V):	24...24V
Voltage Nominal (V):	24
Voltage Forward (Vf):	3
Max. Power Luminaire (W):	42
Max. System Power (W):	46,2
Max. Efficiency Luminaire (lm/W):	92,9
Max. Efficiency System (lm/W):	84,4
Energy Efficiency Class (EU) 2019/2015:	F
Eprel registration number:	2675249

OPERATION AND CONNECTION

Driver Included:	No
Connection (type):	Open Cable End
Length Connection (cm):	500
Min. Ta (°C):	-20
Max. Ta (°C):	125
Operating Temperature:	-20...+125°C
Max. Tc (°C):	125

COLOR AND MATERIAL






Material:	Silicone
Available in special color:	No

MEASUREMENT AND INSTALLATION


Operating Environment:	Indoor / bathroom (ceiling area 1), Indoor / damp locations, Indoor / dry locations, Indoor / wet locations, Outdoor
IP Degree of Protection:	67
Protection Class:	III
Installation:	Surface mounted
Mounting Installation:	Clips, Self Adhesive Tape, Glue, Press Fit
Approval Marks:	CE
Length (mm):	5000
Width (mm):	12
Height (mm):	6
Weight (kg):	0,766

LEDSTRIPS

Min. Bend Radius (mm):	60
Min. Length (m):	0,05
Max. Length (m):	5
Cutting Increments (mm):	50



Hide-a-lite
Heatstrip 24V



8
kWh/1000h



2019/2015