



LITELINE BASIC IP44 600 S 840

Industrial luminaire IP44 in basic model, replaces T5 and T8 luminaires with lower energy consumption and reduced maintenance. Luminaire of coated steel plate. Line prismatic diffuser in impact resistant PC with opal film and smart folding end caps. Push-in terminal, through wiring, one bushing in each end cap and two in the middle, one of which is centred, for concealed cable routing. Perfect when you are looking for a simple solution that does the job – basement storage, laundry rooms or simple industrial premises. Can be adjusted to lower light output and wattage via DIP-Switch Power.

DESCRIPTION

GTIN:	7392971148977
Item Name:	Liteline Basic IP44 600 S 840
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	2100
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Non-replaceable LED, Replaceable Control gear by professional
LED Colour:	White
Colour Temperature (K):	4000
Colour Rendering Index (Ra):	>80
Colour Consistency (SDCM):	4
Luminous Intensity (cd):	721
Beam Angle (°):	103
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	L70 50000h Ta 25°C
Nominal Life Time (h):	50000
Lumen maintenance 50 000h:	L76
LLMF @ 50 000h:	0.76
Life Time Driver:	50 000h/10%
Flicker (PstLM):	1
Stroboscopic effect (SVM):	0,4

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Power LED (W):	16
Max. Power Luminaire (W):	18
Max. System Power (W):	18
Max. Efficiency Luminaire (lm/W):	116,7
Max. Efficiency System (lm/W):	116,7

Containing light source energy efficiency class (EU) 2019/2015: C

OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	DIP-Switch Power, OnOff, Microwave Sensor
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm ²):	5x0,5-2,5
Power Factor λ :	0,9
Efficiency (%):	84
Power loss (W):	3,36
Leakage current (mA) (at 230 V, 50 Hz, full load):	0,5
THD (%):	20
Constant Current (mA):	400
Min. Ta (°C):	-20
Max. Ta (°C):	50
Max. Tc (°C):	85
Suitable for random switching:	Yes
Inrush current (max/time):	15A 400 μ s
Mains surge protection DM (kV):	2
Mains surge protection CM (kV):	2
Fuse B10 (pcs):	40
Fuse B16 (pcs):	64
Fuse C10 (pcs):	64
Fuse C16 (pcs):	90

COLOR AND MATERIAL

Material:	Metal, Plastic
Color:	White
Available in special color:	No

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations
IP Degree of Protection:	44
Protection Class:	I
Installation:	Ceiling, Wall, Surface mounted, Wire-cable installation
Mounting Installation:	Screw Mounting
Approval Marks:	CE
Impact Strength:	IK10
Filament Test IEC 695-2-1(°C):	850
Length (mm):	580
Width (mm):	150
Height (mm):	50
Weight (kg):	1

