



LITELINE G2 IP44 1200 DALI CLO

Highly efficient fluorescent tube replacement with various control options. Body of white enamelled steel sheet metal with folding patented end caps and prismatic cover in durable polycarbonate with an opal diffuser for even light outlet. Both end caps and cover are recycled plastic. Replaceable LED and driver, possible to choose colour temperature and adjust lumen output via DIP-switch. Quick terminal at both ends for simple through wiring. Through wiring 5x2,5mm² as standard. Liteline G2 is perfect where the light requirement is great and the quality requirement is high, such as production environments, garages and industrial premises.

DESCRIPTION

GTIN:	7392971149806
Item Name:	Liteline G2 IP44 1200 DALI CLO
Warranty:	5 years

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	5650
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Replaceable LED by professional, Replaceable Control gear by professional
LED Colour:	Warm White
Colour Temperature (K):	3000, 4000
Colour Rendering Index (Ra):	>80
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	2180
Beam Angle (°):	110
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	h Ta °C
Nominal Life Time (h):	100000
Life Time Driver:	100 000h/20%
Flicker (PstLM):	0,0099
Stroboscopic effect (SVM):	0,0641

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Power LED (W):	33
Max. Power Luminaire (W):	48
Max. System Power (W):	48
Max. Efficiency Luminaire (lm/W):	117,7
Max. Efficiency System (lm/W):	117,7

Containing light source energy efficiency class (EU) 2019/2015: A

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Push 230V, DALI 2
Driver Included:	Yes - replaceable
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm ²):	5x0,5-2,5
Through Wiring:	Yes
Power Factor λ :	0,98
Efficiency (%):	91
Power loss (W):	6
Leakage current (mA) (at 230 V, 50 Hz, full load):	0,7
THD (%):	6
Standby Power:	0,15
Constant Current (mA):	700
Min. Ta (°C):	-25
Max. Ta (°C):	65
Max. Tc (°C):	65
Dimming secondary side:	AM
Suitable for random switching:	Yes
Inrush current (max/time):	35A 170 μ s
Mains surge protection DM (kV):	1
Mains surge protection CM (kV):	2
Fuse B10 (pcs):	20
Fuse B16 (pcs):	30
Fuse C10 (pcs):	30
Fuse C16 (pcs):	45

COLOR AND MATERIAL

Material:	Recycled, Plastic, Sheet metal, Polycarbonate
Color:	White
Environmental Assessment:	Byggvarubedömningen, EPD
Available in special color:	No

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations
IP Degree of Protection:	44
Protection Class:	I
Installation:	Ceiling, Wall, Surface mounted
Mounting Installation:	Screw Mounting
Fire Safety Marks:	D-mark
Approval Marks:	CE, a Hide-a-lite Choice
Impact Strength:	IK10
Filament Test IEC 695-2-1(°C):	850
Length (mm):	1175
Width (mm):	150
Height (mm):	50
Weight (kg):	2,77



