



## LITELINE G2 IP44 1200 DALI CLO

Highly efficient fluorescent tube replacement with various control options. Body of white enamelled steel sheet metal with folding patented end caps and prismatic cover in durable polycarbonate with an opal diffuser for even light outlet. Both end caps and cover are recycled plastic. Replaceable LED and driver, possible to choose colour temperature and adjust lumen output via DIP-switch. Quick terminal at both ends for simple through wiring. Through wiring 5x2,5mm<sup>2</sup> as standard. Liteline G2 is perfect where the light requirement is great and the quality requirement is high, such as production environments, garages and industrial premises.

### DESCRIPTION

<b>GTIN:</b>	7392971149806
<b>Item Name:</b>	Liteline G2 IP44 1200 DALI CLO
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	5650
<b>Light Source:</b>	LED
<b>Replaceability:</b>	Replaceable LED by professional, Replaceable Control gear by professional
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000, 4000
<b>Colour Rendering Index (Ra):</b>	>80
<b>Colour Consistency (SDCM):</b>	3
<b>Luminous Intensity (cd):</b>	2180
<b>Beam Angle (°):</b>	110
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	1
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	h Ta °C
<b>Nominal Life Time (h):</b>	100000
<b>Life Time Driver:</b>	100 000h/20%
<b>Flicker (PstLM):</b>	0,0099
<b>Stroboscopic effect (SVM):</b>	0,0641

## TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Power LED (W):	33
Max. Power Luminaire (W):	48
Max. System Power (W):	48
Max. Efficiency Luminaire (lm/W):	117,7
Max. Efficiency System (lm/W):	117,7

Containing light source energy efficiency class (EU) 2019/2015: A

## OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Push 230V, DALI 2
Driver Included:	Yes - replaceable
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Quick Terminal
Connection (mm <sup>2</sup> ):	5x0,5-2,5
Through Wiring:	Yes
Power Factor $\lambda$ :	0,98
Efficiency (%):	91
Power loss (W):	6
Leakage current (mA) (at 230 V, 50 Hz, full load):	0,7
THD (%):	6
Standby Power:	0,15
Constant Current (mA):	700
Min. Ta (°C):	-25
Max. Ta (°C):	65
Max. Tc (°C):	65
Dimming secondary side:	AM
Suitable for random switching:	Yes
Inrush current (max/time):	35A 170 $\mu$ s
Mains surge protection DM (kV):	1
Mains surge protection CM (kV):	2
Fuse B10 (pcs):	20
Fuse B16 (pcs):	30
Fuse C10 (pcs):	30
Fuse C16 (pcs):	45

## COLOR AND MATERIAL

Material:	Recycled, Plastic, Sheet metal, Polycarbonate
Color:	White
Environmental Assessment:	Byggvarubedömningen, EPD
Available in special color:	No

## MEASUREMENT AND INSTALLATION

<b>Operating Environment:</b>	Indoor / wet locations
<b>IP Degree of Protection:</b>	44
<b>Protection Class:</b>	I
<b>Installation:</b>	Ceiling, Wall, Surface mounted
<b>Mounting Installation:</b>	Screw Mounting
<b>Fire Safety Marks:</b>	D-mark
<b>Approval Marks:</b>	CE, a Hide-a-lite Choice
<b>Impact Strength:</b>	IK10
<b>Filament Test IEC 695-2-1(°C):</b>	850
<b>Length (mm):</b>	1175
<b>Width (mm):</b>	150
<b>Height (mm):</b>	50
<b>Weight (kg):</b>	2,77



