



SPOT UP MULTI 38

Energy-efficient ground light for public environments. Perfect for parks, arenas and industrial properties. Inset LED chip (COB) with modern reflector technology provides a bright and glare-free light. Housing of cast aluminium, outer ring of stainless steel (316) and hardened protective glass. Can be installed in the ground or embedded using the included mounting box. Comes complete with integrated driver, 2 m rubber cable and mounting box.

DESCRIPTION

GTIN:	7392971133171
Item Name:	Spot Up Multi 38
Warranty:	5 years
Type:	.

LIGHT TECHNICAL DATA

Max. Luminaire Lumen (lm):	3800
Light Source:	LED
Light Source Included:	Yes
Replaceability:	Non-replaceable LED and control gear
LED Colour:	Warm White
Colour Temperature (K):	3000
Colour Rendering Index (Ra):	>80
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	7170
Beam Angle (°):	40
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	h Ta °C
Nominal Life Time (h):	80000
Life Time Driver:	50 000h/5%
Flicker (PstLM):	0,01
Stroboscopic effect (SVM):	0,01

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50, 60
Voltage Forward (Vf):	36
Power LED (W):	35,5
Max. Power Luminaire (W):	38
Max. System Power (W):	38
Max. Efficiency Luminaire (lm/W):	100
Max. Efficiency System (lm/W):	100

Containing light source energy efficiency class (EU) 2019/2015: C

OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	OnOff
Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	Cable
Length Connection (cm):	200
Connection (mm ²):	3x1,5
Leakage current (mA) (at 230 V, 50 Hz, full load):	0,62
Min. Ta (°C):	-20
Max. Ta (°C):	80
Max. Tc (°C):	80
Inrush current (max/time):	13,6A 240µs
Fuse C10 (pcs):	29
Fuse C16 (pcs):	46

COLOR AND MATERIAL

Material:	Diecasted, Aluminium
Material Cover Ring:	Stainless Steel
Color:	Stainless Steel

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	67
Protection Class:	I
Installation:	Built-in
Mounting Installation:	Mounting Box
Max. Pressure (kg):	1000
Approval Marks:	CE
Impact Strength:	IK08
Height (mm):	216
Diameter (mm):	240
Weight (kg):	4,35
Height Recessed Part (mm):	255
Height Exterior Part (mm):	3
Built-in Ø (mm):	220mm



40°		3000K	
m	Ø (m)	Emed/Emax	Lux
30m	22.1	3/8	
25m	18.4	5/11	
20m	14.7	8/18	
15m	11.05	13/32	
10m	7.35	30/72	
5m	3.7	121/287	
7170cd			

