
hidealite | Elektro Elco AB Tallvägen 5, 564 35 Bankeryd, Sweden
Phone + 46(0)36 290 60 00 | info@elco.se | www.hidealite.com





CASAMBI ASD

Description

Casambi offers wireless lighting control where devices communicate via Casambi Mesh. A flexible system for controlling luminaires, drivers, sensors, and push buttons, designed for both new and existing lighting installations.

Technical data

Available for various load types and control protocols, such as 230V, 12–24 VDC, DALI, and 0/1–10V. Refer to each specific product for load capacity, power supply, connection, and additional technical specifications.

Measurement and installation

Compact units for easy and flexible installation in or adjacent to luminaires, junction boxes, or flush-mounted boxes. Suitable for both new installations and retrofitting existing lighting solutions.

Controls

Control lighting wirelessly via the Casambi app or with push buttons, and automate control using sensors. Switch on, switch off, and dim lighting, adjust color temperature (Tunable White), control RGB/RGBW, and create lighting scenes.

DESCRIPTION

GTIN:	7392971156507
Item Name:	Casambi ASD
Warranty:	5 years

TECHNICAL DATA

Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50

OPERATION AND CONNECTION

Dimmable:	Yes
Type of Dimming:	Casambi, 0-10V, 1-10V, DALI
Connection (type):	Screw Terminals
Connection (mm2):	2x0,5-1,5
Connection Secondary (type):	Screw Terminals
Secondary Connection (mm2):	2x0,5-1,5
Secondary Outputs (pair):	2
Voltage Output Interval (V):	9-12V
Power Factor λ:	0,6
Power loss (W):	1
Standby Power:	0,9
Current (A):	0,6
Operating Temperature:	-20...+50°C
Max. Tc (°C):	75
Memory Function Power Failure:	Yes
Protection Against:	Short Circuit, Overheating 90°C

COLOR AND MATERIAL

Material:	Plastic
Color:	White

MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / dry locations
IP Degree of Protection:	20
Protection Class:	II
Installation:	Built-in
Mounting Installation:	Screw Mounting
Fire Safety Marks:	Not in insulation without protection cover
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Length (mm):	56,5
Width (mm):	36
Height (mm):	23
Weight (kg):	0,048

