



A

## FOCUS TRACK MINI 60° WHITE 2700K

Stylish anti-glare luminaire in solid and smooth droplet design with integrated mains dimmable driver. The latest LED technology and Comfort Lens provides superb light quality with high luminous comfort and  $RA > 90$ . Suitable for accent lighting or general lighting in most environments. Low-build universal adapter for most 3-phase track systems. Can be complemented with accessories to change light pattern and reduce glare.

### DESCRIPTION

**GTIN:** 7392971127989  
**Item Name:** Focus Track Mini 60° White 2700K

### LIGHT TECHNICAL DATA

<b>Light Source:</b>	LED
<b>Light Source Included (type):</b>	LED not exchangeable
<b>Instant Full Light:</b>	No
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	2700
<b>Colour Rendering Index (Ra):</b>	>90
<b>Colour Consistency (SDCM):</b>	3
<b>Luminous Intensity (cd):</b>	860
<b>Luminaire Lumen (lm):</b>	900
<b>Beam Angle (°):</b>	60
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Direct
<b>Number of Lamps (pcs):</b>	1
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	L70 B10 100 000h Ta 25°C
<b>Nominal Life Time (h):</b>	100000
<b>Life Time Driver:</b>	50 000h/10%

## TECHNICAL DATA

Adjustable:	Yes
Tilttable (°):	90
Rotatable (°):	350
Voltage (type):	AC
Voltage Interval (V):	220...240
Voltage Nominal (V):	230
Power LED (W):	15
Power Luminaire (W):	15
System Power (W):	15
Energy Efficiency Class:	A

## OPERATION AND CONNECTION

Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	3-phase universal adapter
Operating Temperature:	-20...+40
Max. Tc (°C):	85
Dimmable:	Yes
Type of Dimming:	Trailing Edge, Leading Edge
Fuse B10 (pcs):	61
Fuse B16 (pcs):	97
Fuse C10 (pcs):	61
Fuse C16 (pcs):	97

## COLOR AND MATERIAL

Material:	Diecasted, Extruded, Aluminium
Color:	White
Color Code (RAL):	9016
Color Cover Ring:	Black
Color Code Cover Ring (RAL):	9017

## MEASUREMENT AND INSTALLATION

Operation Environment:	Indoor / dry locations
IP Degree of Protection:	20
Installation:	Surface mounted
Mounting Installation:	3-phase Universal Adapter
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Protection Class:	I
Length (mm):	108
Width (mm):	85
Height (mm):	184
Diameter (mm):	85
Weight (kg):	0,72



This LED tracklight contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

**hidealite** Focus Track Mini

874/2012

A++  
A+  
A  
B  
C  
D  
E

LED

