



A+

FOCUS TRACK MAXI 15° WHITE 4000K

Stylish anti-glare luminaire in solid and smooth droplet design with integrated mains dimmable driver. The latest LED technology and Comfort Lens provides superb light quality with high luminous comfort and $RA > 90$. Suitable for accent lighting or general lighting in most environments. Low-build universal adapter for most 3-phase track systems. Can be complemented with accessories to change light pattern and reduce glare.

DESCRIPTION

GTIN: 7392971128177
Item Name: Focus Track Maxi 15° White 4000K

LIGHT TECHNICAL DATA

Light Source:	LED
Light Source Included (type):	LED not exchangeable
Instant Full Light:	No
LED Colour:	White
Colour Temperature (K):	4000
Colour Rendering Index (Ra):	>90
Colour Consistency (SDCM):	3
Luminous Intensity (cd):	8755
Luminaire Lumen (lm):	1995
Beam Angle (°):	15
Light sharing:	Symmetric
Light Outlet:	Direct
Number of Lamps (pcs):	1
Number of LED (pcs):	1
Life Time:	(L70 B10) 100 000h Ta 25°C
Nominal Life Time (h):	100 000
Life Time Driver:	50 000h/10%

TECHNICAL DATA

Adjustable:	Yes
Tilttable (°):	90
Rotatable (°):	350
Voltage (type):	AC
Voltage Interval (V):	220...240
Voltage Nominal (V):	230
Line Frequency (Hz):	50
Power LED (W):	19
Power Luminaire (W):	22
System Power (W):	22
Efficiency LED (lm/W):	105
Efficiency Luminaire (lm/W):	91
Efficiency System (lm/W):	91
Energy Efficiency Class:	A+

OPERATION AND CONNECTION

Driver Included:	Yes
Driver Model:	Constant Current
Driver Type:	Built-in
Connection (type):	3-phase universal adapter
Operating Temperature:	-20...+40
Max. Tc (°C):	85
Dimmable:	Yes
Type of Dimming:	Trailing Edge, Leading Edge
Fuse B10 (pcs):	39
Fuse B16 (pcs):	62
Fuse C10 (pcs):	39
Fuse C16 (pcs):	62

COLOR AND MATERIAL

Material:	Diecasted, Extruded, Aluminium
Color:	White
Color Code (RAL):	9016
Color Cover Ring:	Black
Color Code Cover Ring (RAL):	9017

MEASUREMENT AND INSTALLATION

Operation Environment:	Indoor
IP Degree of Protection:	20
Installation:	Surface mounted
Mounting Installation:	3-phase Universal Adapter
Approval Marks:	CE
Filament Test IEC 695-2-1(°C):	650
Protection Class:	I
Length (mm):	108
Width (mm):	85
Height (mm):	184
Diameter (mm):	85
Weight (kg):	0,72



This LED tracklight contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

hidealite Focus Track Maxi

874/2012

LED

15° 4000K		
m	∅ (m)	Lux Emed/Emax
1m	0.4	3850/8180
2m	0.8	960/2050
3m	1.2	430/910
5m	2.1	150/330

8755cd

