



## SPOTLIGHT GARDEN KIT

Kit with striking mini spots with low energy consumption. Small, adjustable and stylish luminaires for illuminating smaller objects in the garden, such as flower beds or small bushes and trees. Comes with 0.5 m rubber cable with screw connector and ground spike. The kit comprises 2x IP67 luminaires, 2x ground spikes, 2x T-connectors, 1x 1 m extension cable with quick connector and 1x plug-in transformer IP44 with 5 m cable. Can be combined with Decklight Garden thanks to the common coupling system.

### DESCRIPTION

<b>GTIN:</b>	7392971130149
<b>Item Name:</b>	Spotlight Garden Kit
<b>Warranty:</b>	5 years

### LIGHT TECHNICAL DATA

<b>Max. Luminaire Lumen (lm):</b>	40
<b>Light Source:</b>	LED
<b>Light Source Included:</b>	Yes
<b>Replaceability:</b>	Non-replaceable LED, Replaceable Control gear by end-user
<b>LED Colour:</b>	Warm White
<b>Colour Temperature (K):</b>	3000
<b>Colour Rendering Index (Ra):</b>	>80
<b>Colour Consistency (SDCM):</b>	3
<b>Luminous Intensity (cd):</b>	2x150
<b>Beam Angle (°):</b>	36
<b>Light sharing:</b>	Symmetric
<b>Light Outlet:</b>	Indirect
<b>Number of Lamps (pcs):</b>	1
<b>Number of LED (pcs):</b>	1
<b>Life Time:</b>	L70 50000h Ta 25°C
<b>Nominal Life Time (h):</b>	50000
<b>Lumen maintenance 50 000h:</b>	L70
<b>LLMF @ 50 000h:</b>	0.7
<b>Life Time Driver:</b>	50 000h/10%

## TECHNICAL DATA

Adjustable:	Yes
Tilttable (°):	90
Rotatable (°):	360
Voltage (type):	AC
Voltage Interval (V):	220...240V
Voltage Nominal (V):	230
Line Frequency (Hz):	50
Voltage Forward (Vf):	0,8
Max. Power Luminaire (W):	0,8
Max. System Power (W):	2,1
Max. Efficiency Luminaire (lm/W):	50
Max. Efficiency System (lm/W):	19,0

## OPERATION AND CONNECTION

Dimmable:	No
Type of Dimming:	OnOff
Driver Included:	Yes
Driver Model:	Constant Voltage
Driver Type:	Stand Alone
Connection (type):	Cord Set
Min. Ta (°C):	-15
Max. Ta (°C):	40
Max. Tc (°C):	40

## COLOR AND MATERIAL

Material:	Aluminium
Color:	Aluminum
Environmental Assessment:	Byggvarubedömningen

## MEASUREMENT AND INSTALLATION

Operating Environment:	Indoor / wet locations, Outdoor
IP Degree of Protection:	44
Protection Class:	III
Installation:	Surface mounted
Mounting Installation:	Screw Mounting, Ground Spike
Approval Marks:	CE
Impact Strength:	IK10
Length (mm):	70
Height (mm):	70
Diameter (mm):	30
Weight (kg):	0,75



